Product data sheet 6004 CT-3 EAN-No. 4000896260027



Length: 196 mm · Torque range min-max: 0.02 – 0.3 Nm · Accuracy: 6 % · 🚳



- "Ratchet function" with free-running mechanism, featuring right · left · fixed switching · enables fast work thanks to smooth re-gripping when operating screw connections, even in confined installation spaces
- Excellent readability of the torque setting thanks to large, clear numerical display
- Short 36° release distance with ergonomic release behaviour and clearly audible signal
- Bit holder with quick-release fastener fast bit change with one hand
- Release mechanism made of high-alloy tool steel with excellent wear resistance
- Exceeding the set torque is prevented by the overload clutch ("slipper")
- Easily recognisable locking status by means of lock symbols
- · With calibration certificate and serial number
- Calibration and repair capability at the HAZET Service Centre in Remscheid
- Ergonomically shaped HAZET 2-component handle
- Tested in accordance with DIN EN ISO 6789-2:2017
- · Made in Germany
- Output: 🗐 🕫
- Dimensions: 196 mm
- For manual operation
- Torque range min-max: 0.02 0.3 Nm
- Accuracy: 6 %
- Scale Graduation (Nm): 0.2 cNm

Handle Order Number Ergonomically shaped HAZET 2-component handle 6004 CT-3