

Product data sheet

9098/24 EAN-No. 4000896**258086**



24-pieces



Application:

Gentle removal of seized diesel injectors without force

- Avoidance of damage to cylinder head/cylinder head cover due to high forces from supports

Contents:

- Diesel injector distorter · Compressed air
- Extension for deep-seated injectors or installed installation spaces
- Universal claw
- 21 adapters:
 - Thread M8 x P1.0
 - Thread M8 x P1.25
 - Thread M10 x P1.0
 - Thread M10 x P1.5
 - Thread M14 x P1.0
 - Thread M14 x P1.5 (**DELPHI**)
 - Thread M16 x 1.0 (**TOYOTA**)
 - Thread M17 x P1.0 (**BOSCH 110**)
 - Thread M18 x P0.75 (**BOSCH 120**)
 - Thread M18 x P1.5 (**UNIVERSAL**)
 - Thread M20 x P1.0 (**DENSO / A**)
 - Thread M25 x P0.5 (**DENSO**)
 - Thread M25 x P1.0 (**BMW · BOSCH · FIAT · MERCEDES-BENZ · PSA · PSAW · RENAULT · SIEMENS**)
 - Thread M26 x P0.75 (**BOSCH CRIN 2**)
 - Thread M27 x P0.75
 - Thread M27 x P1.0 (**SIEMENS**)
 - Thread M27x P1.0 (**SIEMENS**)
 - Thread M29 x P1.0
 - Thread M31 x P0.75 (**BOSCH CRIN 1**)
 - Inside thread M12(F) x P1.5 · Outside thread M20(M) x P1.5
 - Inside thread M14(F) P1.5 x Outside thread M22(M) x P1.5
- Increased pulse energy: 30 mm working path
- Easy assignment: adapter including labelling with thread information
- Convenient and safe operation of the unit: on/off switch on flexible hose
- Anti-twist protection: hose decoupled and rotatable by 360°

Product data sheet

9098/24

EAN-No. 4000896258086



- Everything included: set including air connection nipple for the German market
- Plastic box
- Number of tools: 24

Order Number

9098/24



9098-A1



9098-A2



9098-A3



9098-B1



9098-B2



9098-B4



9098-B5



9098-B6



9098-C1



9098-C2



9098-C3



9098-C4



9098-C5



9098-D1



9098-D2



9098-D3



9098-D4



9098-D5



9098-D6



9098-E1



9098-E2