

## **Product information**

## 88 05 300

## **KNIPEX Alligator®**

Water Pump Pliers

**DIN ISO 8976** 



- Good access to the workpiece due to slim size of head and joint area
- More output and comfort compared to conventional water pump pliers of the same length: 9-notch adjustment positioning for 30 % more gripping capacity
- Self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- Gripping surfaces with special hardened teeth, teeth hardness approx.
  61 HRC: high wear resistance and stable gripping
- Box-joint design for high stability due to double guide
- Robust construction, insensitive to dirt; particularly suitable for outdoor work
- Pinch guard prevents operators' fingers being pinched



300
773042389
ne-plated
ne-plated
nulti-component grips
51 x 22 mm
SO 8976
7

Technical details	
Adjustment positions	9
Capacity for pipes, inches (diameter)	Ø 2 3/4 Inch
Capacities for nuts	60 mm
Capacities for pipes (diameter)	Ø 70 mm


does not contain SVHC

not applicable

technical change and errors excepted

**REACH** compliant

RoHS compliant













Self-locking on pipes and nuts: no slipping on the workpiece; the complete actuating force can be used to turn the workpieces; not having to squeeze the pliers handles reduces the required effort



