

Product information

95 12 500

Cable Shears



- Low weigth, high leverage
- Low handforce required due to favourable lever ratio and special blade geometry
- For cutting copper and aluminium single conductors as well as multiple stranded cables
- Precision-ground, hardened blades
- Clean and smooth cut without crushing and deformation
- Not suitable for steel wire and wire ropes
- Pinch guard prevents operators' fingers being pinched
- Adjustable bolted joint

General

Article No.95 12 500EAN4003773069966HeadburnishedHandleswith multi-component gripsWeight1,090 gDimensions500 x 160 x 35 mmREACH compliantcontains SVHCRoHS compliantnot applicableCutting capacity copper cable, multiple- stranded150 mm²AWG6/0		
HeadburnishedHandleswith multi-component gripsWeight1,090 gDimensions500 x 160 x 35 mmREACH compliantcontains SVHCRoHS compliantnot applicableCutting capacity copper cable, multiple- strandedStrandedØ 27 mm	Article No.	95 12 500
Handleswith multi-component gripsWeight1,090 gDimensions500 x 160 x 35 mmREACH compliantcontains SVHCRoHS compliantnot applicableCutting capacity copper cable, multiple- strandedCutting capacity copper cable, multiple- stranded150 mm²Cutting capacity copper cable, multiple- stranded0 27 mm	EAN	4003773069966
Weight1,090 gDimensions500 x 160 x 35 mmREACH compliantcontains SVHCRoHS compliantnot applicableCutting capacity copper cable, multiple- strandedCutting capacity copper cable, multiple- stranded150 mm²StrandedØ 27 mm	Head	burnished
Dimensions500 x 160 x 35 mmREACH compliantcontains SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- stranded150 mm²Cutting capacity copper cable, multiple- stranded0 27 mm	Handles	with multi-component grips
REACH compliantcontains SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- stranded150 mm²Cutting capacity copper cable, multiple- stranded0 27 mm	Weight	1,090 g
RoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- stranded150 mm²Cutting capacity copper cable, multiple- strandedØ 27 mm	Dimensions	500 x 160 x 35 mm
Technical details Cutting capacity copper cable, multiple- stranded 150 mm² Cutting capacity copper cable, multiple- stranded Ø 27 mm	REACH compliant	contains SVHC
Cutting capacity copper cable, multiple- stranded 150 mm ² Cutting capacity copper cable, multiple- stranded Ø 27 mm	RoHS compliant	not applicable
stranded Ø 27 mm stranded Ø 27 mm	Technical details	
stranded		150 mm ²
AWG 6/0		Ø 27 mm
	AWG	6 / 0

technical change and errors excepted

