

Product information

95 17 200

Cable Shears

With twin cutting edge

IEC 60900 DIN EN 60900



⚡ 1000 V

- Clean and smooth cut without crushing and deformation
- By dividing the cutting actions into initial cut (insulating sheath in the front cutting area) and final cut (conductor in the back cutting area), cables up to Ø 20 mm can be cut in one-hand operation
- Pinch guard prevents operators' fingers being pinched
- For cutting copper and aluminium cables up to Ø 20 mm (70 mm²)
- Not suitable for steel wire and hard drawn copper conductors
- Precision-ground, hardened blades
- Low handforce required due to favourable lever ratio and special blade geometry
- Adjustable bolted joint, self-retaining screw

General

Article No.	95 17 200
EAN	4003773026952
Shears	chrome-plated
Handles	with dipped insulation, VDE-tested
Weight	360 g
Dimensions	200 x 80 x 34 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Cutting capacity copper cable, multiple-stranded	70 mm ²
Cutting capacity copper cable, multiple-stranded	Ø 20 mm
AWG	2 / 0
VDE tested	yes

technical change and errors excepted



Final cut: after cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible.



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.